

SAFETY DATA SHEET (SDS)

Section 1. Identification					
Product identifier	PROSOL				
Other means of identification 797					
Recommended use and restrictions on use		CLEANER AND DEGREASER FOR MECHANICALS PARTS			
Initial supplier identifier	PROLAB TECHNOLUB INC. 4531 RUE INDUSTRIELLE, THETFORD MINES, (QUEBEC), G6H 2J				
CANADA TEL. (418) 423-2777 FAX : (418) 423-7619					
Emergency telephone num	ber/restriction o	n use Canada – CANUTEC 24 hour number 613-996-6666			
Section 2. Hazard identification					
Classification of hazardous product (name of the category or subcategory of the hazard class)					
Corrosive to metals (Category 1)					

Corrosive to metals (Category 1) Skin corrosion (Category 1C)

Serious eye damage (Category 1)

Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)



Danger

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

P234 Keep only in original packaging. P260 Do not breathe dusts or mists. P264 Wash hands/nails/face thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P363 Wash contaminated clothing before reuse. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310 Immediately call a doctor. P390 Absorb spillage to prevent material-damage. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

container in acce	raunce with rocal, regional of national regulation					
Other hazards	known None					
Section 3. Composition/information on ingredients						
Chemical name (common name/synonyms)		CAS number or other	Concentration (%)			
Polyethylene glycol octylphenyl ether		9036-19-5	3-7			
2-Butoxyethanol		111-76-2	3-7			
Sodium hydroxide		1310-73-2	~1			
Section 4. First-aid measures						
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a doctor.					
Ingestion	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. NEVER give anything by mouth if victim is rapidly losing					
	consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses of water. If					
	vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a doctor if you feel unwell.					
Skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (15-20 minutes). Wash					
	contaminated clothing before reuse.					
Eye contact	IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue					
rinsing.						
Most important symptoms and effects (acute or delayed)		Causes severe skin burns and eye damage.				
Indication of immediate medical attention/special treatment In all cases, call a doctor. Do not forget this document.						
Section 5. Fire-fighting measures						
Specific hazards of the hazardous product (hazardous combustion products)						
Carbon oxides a	nd other irritant/toxic gases and fumes.					
Suitable and unsuitable extinguishing media						
In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish surrounding products.						
Special protecti	ve equipment and precautions for fire-fighters	8				

protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper



Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Absorb spillage to prevent material-damage. Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).

Methods and materials for containment and cleaning up

Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

Section 7. Handling and storage

Precautions for safe handling

May be corrosive to metals. Keep only in original packaging. Wear protective gloves/ protective clothing/ eye protection/ face protection. Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with every skin and elething. Keep away from host sprays and flame. Avoid generating high concentrations of dusts vapours or mists. Keep

contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

Section 8. Exposure controls/Personal protection

Control parameters (biological limit values or exposure limit values and source of those values)

Exposure limits: CAS 111-76-2 ACGIH-TWA 20 ppm & PEL-TWA 50 ppm; CAS 1310-73-2 ACGIH-TWA 2 mg/m^3 (ceiling) & PEL-TWA 2 mg/m^3

Appropriate engineering controls

Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Individual protection measures/personal protective equipment

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.

Section 9. Physical and chemical properties						
Appearance, physical state/colour Yellow liquid	Vapour pressure Not available					
Odour Charateristic	Vapour density Not available					
Odour threshold Not available	Relative density 1					
pH 12	Solubility Soluble					
Melting/freezing point 0°C	Partition coefficient - n-octanol/water Not available					
Initial boiling point/range Not available	Auto-ignition temperature Not available					
Flash point > 93°C	Decomposition temperature Not available					
Evaporation rate Not available	Viscosity 2.3 cSt @ 40°C					
Flammability (solids and gases) Not available	VOC Not available					
Upper and lower flammability/explosive limits Not available	Other None known					
Section 10 Stability and reactivity						

Section 10. Stability and reactivity

Reactivity

Does not react under the recommended storage and handling conditions prescribed.

Chemical stability

Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

When mixed with incompatible materials.

Conditions to avoid (static discharge, shock or vibration)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

Incompatible materials

Oxidizing materials; acids; etc.

Hazardous decomposition products

None known



Section 11. Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)

Causes severe skin burns and eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Skin burn, redness, stinging, pain; Eye burn, redness, tearing; Digestive tract burn; Respiratory tract burn, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.

Delayed and immediate effects (chronic effects from short-term and long-term exposure)

Skin Sensitization – No data available;

Respiratory Sensitization – No data available;

Germ Cell Mutagenicity – No data available;

Carcinogenicity - No ingredient listed by IARC, ACGIH, NTP or OSHA Reproductive Toxicity - No data available;

Specific Target Organ Toxicity — Single Exposure – No data available; Specific Target Organ Toxicity — Repeated Exposure – No data available;

Aspiration Hazard – No data available;

Health Hazards Not Otherwise Classified - No data available.

Numerical measures of toxicity (ATE; LD₅₀ & LC₅₀)

CAS 9036-19-5 LD₅₀ Oral, Rat 4190 mg/kg; CAS 111-76-2 LD₅₀ Oral, Rat 917 mg/kg; LC₅₀ Inhalation, Rat (4 h) 450 ppm; LD₅₀ Dermal, Rabbit 220 mg/kg;

ATE not available in this document.

Section 12. Ecological information

Ecotoxicity (aquatic and terrestrial information) No data available

Persistence and degradability No data available

Bioaccumulative potential No bioaccumulation is to be expected.

Mobility in soil No data available

Other adverse effects No data available

Section 13. Disposal considerations

Information on safe handling for disposal/methods of disposal/contaminated packaging

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Section 14. Transport information

UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations

UN1824; SODIUM HYDROXIDE SOLUTION; CLASS 8; PG III

UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)

UN1824; SODIUM HYDROXIDE SOLUTION; CLASS 8; PG III

UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)

UN1824; SODIUM HYDROXIDE SOLUTION; CLASS 8; PG III

Special precautions (transport/conveyance) May also be shipped as a LIMITED QUANTITY in accordance with TDG.

Environmental hazards (IMDG or other) None

Bulk transport (usually more than 450 L in capacity) Possible

Section 15. Regulatory information

Safety/health Canadian regulations specifics Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).

Refer to Section 3 for ingredient(s) of the DSL **Environmental Canadian regulations specifics**

Safety/health/environmental outside regulations specifics

United States OSHA information: This product is regulated according to OSHA (29 CFR).

United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14. United States TCSA information: Refer to the ingredients listed in Section 3.

National Fire Protection Association (NFPA):

FLAMMABILITY: 1 INSTABILITY: 0 SPECIAL HAZARDS: Refer to Section 2 & 3. HEALTH: 3

HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

California Proposition 65: This product may contain traces of a material known to the State of California to cause cancer or other reproductive harm.



Section 16. Other information					
Date of the latest revision of the safety data sheet June 21, 2024.					
References	Safety Data Sheets from manufacturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.				
Abbreviations					
ACGIH	American Conference of Governmental Industrial Hygienists				
ATE	Acute toxicity estimate				
CAS	Chemical Abstract Service				
DSL	Domestic Substance List				
IARC	International Agency for Research on Cancer				
IATA	International Air Transport Association				
IMDG	International Maritime Dangerous Goods Code				
LC	Lethal concentration				
LD	Lethal Dosage				
NIOSH	National Institute for Occupational Safety and Health				
NTP	National Toxicology Program (U.S.A.)				
OSHA	Occupational Safety and Health Administration (U.S.A.)				
PEL	Permissible Exposure Limit				
STEL	Short-term Exposure Limit				
TDG	Transport of dangerous goods in Canada				
TLV	Threshold Limit Value				
TSCA	Toxic Substances Control Act				
TWA	Time Weighted Average				
WHMIS	Workplace Hazardous Materials Information System				

The information presented herein has been compiled from sources considered dependable and is accurate to the best of **PROLAB TECHNOLUB INC.**'s knowledge. **PROLAB TECHNOLUB INC.** Makes no warranty whatever expresses or implied of merchantability or fitness for the particular purpose. The information relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Customers are encouraged to conduct their own tests. Before using the product, read its label. **PROLAB TECHNOLUB INC.** Assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.